



Kraftkolour Pty Ltd
Factory 2, 99 Heyington Ave
THOMASTOWN Vic 3074
Tel: 1300 720 493
Web: Kraftkolour.net.au

SAFETY DATA SHEET

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name: **Shimmer Paints: Assorted Colours**

Other Name(s): n/a

Recommended Use: For use as a Craft Paint

Supplier: Kraftkolour Pty Ltd
ABN: 85 007 291 303
Street Address: 2/99 Heyington Ave
Thomastown Victoria, Australia 3074

Telephone Number: +61 3 9460 6432
Fax Number: n/a
Website: www.kraftkolour.net.au

Emergency Numbers: 000 Police, Fire and Ambulance
131 126 For poisons advice contact a Poisons Information Centre
(New Zealand 0800 764 7660) or a Doctor at once.

2. HAZARDS IDENTIFICATION

Not hazardous according to the criteria set out by ASCC (NOHSC) based on currently available information.

Not classified as Dangerous Goods according to the criteria of the Australian Dangerous Goods Code for transport by Rail or Road.

Poisons schedule: Not classified.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Substance	CAS#	Proportion %	Risk Phrase(s)
Acrylic Polymer(s)		30 – 50	-
Water	7732-18-5	20 – 40	-
Pigment Colours	1333-86-4	< 9	-
Mica Pigment	12001-26-2	< 11	
Titanium Dioxide	13463-67-7	< 1	
Ingredients deemed not to be hazardous at level used		up to 100%	

4. FIRST AID MEASURES

Swallowed	If swallowed do not induce vomiting. Give a glass of water and seek medical attention.
Eye	Immediately open eye and flush with plenty of running water for at least 15 minutes. Seek medical attention.
Skin	Remove contaminated clothing and wash affected area with plenty of soap and water.
Inhalation	Remove victim to fresh air, remove any contaminated clothing to prevent further exposure. Keep victim warm. If symptoms persist seek medical attention.
Medical Advice	Treat symptomatically.

5. FIRE FIGHTING MEASURES

Suitable Extinguishing Media:	Water fog or spray, foam, Carbon Dioxide or Dry Chemical Powder.
Hazards from Combustion Products:	Material is not combustible once the water component has evaporated. The residual material can burn if ignited and will produce toxic fumes.
Special Protective precautions and equipment for Fire fighters:	Breathing apparatus should be worn to protect against any potential toxic fumes that may be present.
Hazchem Code:	None allocated.

6. ACCIDENTAL RELEASE MEASURES

Emergency Procedures:	If waterways or sewers become contaminated with product advise the local authorities of the contamination.
Methods and Materials for containment and clean up:	Do not contaminate the waterways or sewer with spill. Do not flush into drains and sewer. If sewer or waterway becomes contaminated contact the local authority. Dike and contain spill with sand, earth or an absorbent material. Clean up before material dries. Place collected material in an appropriate container and dispose of material in accordance with the local authority.

7. HANDLING AND STORAGE

Precautions for Safe Handling:

Keep out of the reach of children.

Avoid contact with eyes or mouth and avoid repeated prolonged contact with skin.

Conditions for Safe Storage:

Store in a cool dry place out of direct sunlight. Containers should be sealed when not in use and should be checked on a regular basis for signs of damage or leaks.

8. PERSONAL PROTECTION / EXPOSURE CONTROL

Protective Equipment:



Personal:

Normal working clothes covering arms and legs, eyewash facility and emergency shower. Avoid repeated prolonged contact.

Gloves:

PVC Coated.

Eyes:

Goggles (AS1337).

Respiratory: Use with adequate ventilation. If applying via spray and approved respirator is recommended (AS1716 approved type).

Other: Practice strict hygiene – wash hands before breaks and after finishing.

National Exposure Limits:

No value assigned to this specific material according to ASCC.

Biological Limit Values:

No value assigned to this specific material according to ASCC.

Engineering Controls: Adequate ventilation should be provided at all times and avoid heating product.

9. PHYSICAL AND CHEMICAL PROPERTIES

Property	Units	Result
Physical State		Viscous Liquid
Colour		Various Coloured Liquids
Odour		Slight Ammoniacal Odour
PH		8.5 – 9.5
Vapour Pressure		N/A
Vapour Density		N/A
Boiling Point	°C	100
Freezing Point	°C	0
Solubility		Miscible with Water
Specific Gravity	Kg/Lt	1.02 – 1.10
Flash Point	°C	N/A
Upper Flammability Limit	°C	N/A
Lower Flammability Limit	°C	N/A
Auto Ignition Temperature	°C	N/A
Volatile Organic Content	%	5

10. STABILITY AND REACTIVITY

Chemical Stability:	Stable under normal use conditions.
Conditions to Avoid:	Avoid repeated contact with person, contact with food and high temperature conditions with sealed containers.
Incompatible Materials:	No information available
Hazardous Decomposition Products:	No information available
Hazardous Reactions:	No information available

11. TOXICOLOGICAL INFORMATION

If used in accordance with the manufacturer's recommendations and this Material Safety Data Sheet no negative health results should occur. If exposure results in symptoms, the following may be observed:

Acute and Chronic Exposure and Routes of Exposure

Acute:	No information Available on product
Chronic:	No information available on product

11. TOXICOLOGICAL INFORMATION, continued

Routes of Exposure

General:	Large amounts may result in vomiting and nausea. Small amounts should not result in any expected reactions.
Eyes:	Irritation may occur.
Respiratory System:	If excess inhalation occurs headache, nausea or irritation to respiratory tract may occur.
Skin:	Irritation may occur.
Long Term Effects:	No information is available for this product currently.
Toxicological Information:	No LD ₅₀ Value has been determined for this product.
Toxicological Information	No information is available for this product currently for product components

12. ECOLOGICAL INFORMATION

Ecotoxicity:	Avoid contaminating the sewer system and waterways.
---------------------	---

13. DISPOSAL INFORMATION

Disposal Methods:

Small:	Unwanted paint should not be disposed of down the drain system but instead should be brushed out on newspaper and allowed to dry. This can then be disposed of via the domestic waste collections. The empty paint containers should be allowed to dry out and disposed of in accordance with the recommendations of the local authorities.
Large:	The disposal of large quantities of paint must be handled by a licensed waste handling contractor and can normally be disposed of at a licensed landfill waste site

14. TRANSPORT INFORMATION

UN Number:	None allocated
UN Proper Shipping Name:	Paint
Class and Subsidiary Risk(s):	None allocated
Packing Group:	None allocated
Special Precautions for User:	Avoid transporting with oxidising materials in close proximity
Hazchem Code:	None allocated
Not classified as a DANGEROUS GOOD according to the Australian Dangerous Goods Code for Transport via Road and Rail. Not regulated for IATA	

15. REGULATORY INFORMATION

Hazard Status:	Not classified as Hazardous according to the criteria for ASCC (NOHSC) based on currently available information.
Poisons Schedule:	No Poisons Schedule applicable.
Risk Phrase(s):	Not hazardous according to the criteria set out by ASCC (NOHSC) based on currently available information
Safety Phrase(s):	as above
AICS:	All materials contained in this product appear in the AICS (Australian Inventory of Chemical Substances) database.

16. OTHER INFORMATION

This SDS summarises our best knowledge of the health and safety hazard information of the product and how to safely handle and use the product in the workplace. Each user should read this SDS and consider the information in the context of how the product will be handled and used in the workplace, including in conjunction with other products.

Kraftkolour P/L cannot anticipate or control the conditions under which this information may be used. Each user should review the information in the specific context of the intended application. Kraftkolour P/L will not be responsible for damages of any nature resulting from the use of or reliance upon this information. No expressed or implied warranties are given other than those implied by Commonwealth, State or Territory Legislation

Kraftkolour P/L – Issue date: 1/11/2019 Tel: 03 9460 6432